

Silica Fume – Floors & Pavements

For Building, Construction, Mining & Tunnelling

SILICA FUME FLOOR AND PAVEMENT CONCRETE

Silica Fume FPC can include a range of specialist materials for industrial floors, housing slabs, pavements and agricultural hard stands:

- Scancem steel fibres to replace and improve on conventional reinforcing
- Synthetic fibres to provide early age crack control (up to 1 day)
- Silica Fume to give high abrasion resistance, strength and chemical resistance
- Pigments for a brighter finish or an environmentally sensitive appearance

ABRASION RESISTANCE

The abrasion resistance of concrete is closely linked to the strength of the cement paste. This can be improved by using a lower water:cement ratio, reducing bleed (reduces the water:cement ratio at the surface), and by adding Silica Fume. Bleed can have a major affect on abrasion resistance. Silica Fume virtually eliminates bleed, synthetic fibres reduce it significantly.

IMPACT RESISTANCE

Impact Resistance is a measure of the ability of the concrete to absorb the energy imparted to it by a sharp, short duration load or blow. Fibres enable concrete to absorb the energy by turning it

from a brittle material to a tougher more ductile one. The level of improvement is determined by the fibre type, geometry and dosage.

Synthetic fibres give the highest level of impact resistance to concrete and are therefore of value:-

- In heavy equipment workshops
- In addition to Silica Fume where abrasion and impact are present
- Where tracked vehicles are used
- Where rocks, rubble or rubbish are loaded
- Where vibration is a problem
- Where steel wheeled trolleys, rubbish dumpsters etc are use

PLASTIC CRACKING

When the concrete is fresh and still plastic i.e. in the first few hours after placing, various factors can cause early age tensile strains which exceed the tensile capacity of the young concrete. Low dosages of synthetic fibres will increase the resistance of concrete to this type of cracking. Performance is related to the fibre characteristics but, in general, synthetic fibres are superior to steel fibres in controlling plastic cracking because the comparatively low steel fibre count per kilo of fibres added results in a much lower fibre/paste bond area that cannot effectively mobilise the

load carrying capacity of steel fibres at early age.

Early age strains that are of significance are plastic shrinkage, early thermal and plastic settlement. Drying shrinkage cracking, the majority of which occurs from 1 day to 90 days can not be controlled by synthetic fibre because the concrete strength and modulus are far higher than the fibres. Long term strains are best controlled by steel fibre.

TOUGHNESS

Toughness is the principal criteria for designing industrial floor slabs. The design is based on the fact that the concrete will behave in a ductile fashion with the steel fibres spreading the load into the surrounding concrete, and hence over a larger spread of ground. Toughness is a standard measure for steel fibre concrete and is the subject of ASTM, JIS and many European standards. The Concrete Society (UK) has maintained the JIS defined Re₃ designation of toughness as being suitable for floor slab design in its Technical Report 34.

The performance of fibres varies enormously depending on the steel properties, anchorage design and aspect ratio. Scancem is the leading fibre in terms of toughness performance.

TENSILE STRENGTH

Fibres do not increase tensile strength significantly. Conventionally 30Mpa concrete is taken to have a flexural

Silica Fume Concrete – The Next Generation Construction Material

strength of 4Mpa. In some steel fibre slab design methods a flexural strength of 6Mpa as the principal criteria used in the elastic design. This can simply be achieved by increasing the compressive strength of the concrete to 40Mpa by lowering the w/c ratio or by using Silica Fume. In other words the steel fibre is redundant. This shows the method is invalid and a toughness basis should be used.

SHEAR STRENGTH

Steel fibres provide shear capacity because many of the fibres are under a steep angle and act like stirrups in direct tension. Hence, if the slab cracks, the steel fibres will provide a locking action that prevents differential vertical movement.

Scancem steel fibres provide excellent shear capacity and hence 30kg/m³ of 60/1.00mm fibre were specified. The Silica Fume FPC with Scancem steel fibres was pumped to the job site with ease.

CONSTRUCTABILITY

Use of steel fibres and silica fume can make construction considerably easier and cheaper. Where steel fibres are used to replace mesh the cost and time saving associated with not placing mesh are considerable. Another benefit is that without mesh its often possible to truck the concrete up to the work face, no pumping or wheelbarrowing involved. A big decision, what joint spacing? In Europe jointless floors (40 metre plus joint centres) are not uncommon. This requires a high degree of

expertise and specialist design. More generally steel fibre floor slabs enable joint spacing to be increased. It is recommended that the slabs are allowed to move and thickened sections should be isolated from large pours.

Silica Fume Concrete requires close attention to ensure plastic cracking, due to the low bleed does not occur. This low bleed can be an advantage, in that finishing can be undertaken immediately with the one pass finish method.

SUGGESTED READING

1. Holland, T.C., "Abrasion-Erosion Update", Concrete Structures, Repair and Rehabilitation, Vol C-38-1, August 1983, pp 1-3,7.
2. Carlsson, M., Hope, R., Pedersen, J., "Use of Condensed Silica Fume (CSF) in Concrete", ACI SP-91, CANMET/ACI Second International Conference on the Use of Fly Ash, Silica Fume, Slag and Natural Pozzolans in Concrete, April 1986, Madrid, Vol 11, Detroit, American Concrete Institute, 1986, pp1013-1030.
3. Gjorv, O.E., Baerland, T., and Heinrich, R.R., "Abrasion Resistance of High Strength Concrete Pavements. Concrete International Vol 12 No 1, January 1990.
4. Gjorv, O.E., Baerland, T., Tønning, H.R., "High Strength Concrete for

Highway Pavements and Bridge Decks", Division of Building Materials, University of Trondheim, Report No 87.202, Trondheim, Norway, 1987.

5. Hester, W.T., "Specifying High Performance Concrete Industrial Floors", construction Specifier, 1986.
6. "The Structural Design of Heavy Duty Pavements for Ports and Other Industries", British Ports Federation.
7. "High Performance Concretes, A State of the Art Report", Strategic Highway Research Program, National Research Council, SHRP-C/FR-91-103, 1991.
8. Baluguru. P., and Shah S.P., "Fibre Reinforced Composites" Me Graw Hill 1992.

The information given is based on knowledge and performance of the material Every precaution is taken in the manufacture of the product and the responsibility is limited to the quality of supplies, with no guaranty of results in the field as Scancem Materials has no control over site conditions or execution of works

SCANCEN MATERIALS

Products For Engineered Concrete

S'pore : 190 Macpherson Rd, #06-03D, Wisma Gulab, S348548 Tel: +(65) 67489808 Fax: +(65) 67480360 email info@scancemmaterials.com
M'sia : A-4-9, Plaza Dwi Tasik, Jln Sri Permaisuri, Bandar Sri Permaisuri 56000 Kuala Lumpur, Tel: +(60) 3 9171 2110 Fax: +(60) 3 9171 5110